

GENESIS Pedicure Spa

Raising the standards for Technician Comfort

The Genesis provides the comfort and luxury your clients will love, with the ease of use your technicians need. The seat and bowl raise and lower adjusting to a comfortable height of the technician. The Shiatsu massage gives this chair the relaxing experience your clients expect. Purely Simple Pipeless system makes sanitizing between clients effortless.




Shiatsu chair is equipped with convenient flip up manicure trays and deep cup holders that accent graceful arm styling.



Client controls chair positioning and recline, along with massage settings via easy-to-use remote control.

Intuitively placed controls and independently adjustable leg rests provide technician comfort.



SPA INFORMATION

Hot and cold water supply lines required (hot and cold shut offs may be installed under pedicure spa base)

Pedicure spa must be installed by a licensed electrician and a licensed plumber, conforming to all local and national electrical and plumbing codes

All dimensions and weights are approximate.

Whirlpool pump motor: 120V / 60HZ / 1Amp

Water Fill Line Capacity: 5 U.S. gallons (19 Liters)

Seat upholstery: Polyurethane

Seat and back motors: 24V DC Linear Actuators.

Power source: 120V / 60HZ / 7.5Amp / 900W

Construction: Steel Frame with ABS-backed acrylic shells, glass basin, pre-plumbed

Technology: 2 water massage channels, no closed loop circulating pipes, fully drained. System employs three part assembly that twists from the basin for easy cleaning.

Electrical switches: On/Off switch for pump. Single hand-held, low voltage remote controls for massage motors and seat forward/back position. Hot and Cold water supply lines required.

Compliances: Conforms to UL STD 1951. Certified to CAN/CSA Std C22.2 No. 68

Also classified in accordance with: ASME A112.18.3-2002(R2008) ASME A112.18.1-2012/CSA B125.1-12

Electrostatic Limits: This unit may lose one or more functions when electrostatic contact discharge in excess of 4KV gets into accessible conductive part of the unit and can be restored by resetting the unit.

AC input power port and can be restored by resetting the unit. This unit may lose one or more functions when subjected to fast transient voltages in excess of 0.5KV at 5 KHz repetition frequency and cannot be restored.

Limited warranty: 2 year limited parts warranty on all components.

All dimensions and weights are approximate.

SHIPPING INFORMATION

Genesis Shipping Dimensions (spa only with seat collapsed):
56"L (142cm) x 32"W (81cm) x 34"H (86cm)

Shipping Dimensions (Spa with seat collapsed, carton, and pallet):
67"L (170cm) x 38"W (96cm) x 43"H (109cm)

Weight:
350 lbs. (160kgs) - Spa
400 lbs. (182kgs) - Spa, carton, and pallet

Overall dimensions, seat upright and forward:
57"L (145cm) x 31"W (79cm) x 55"H (140cm)

Minimum area required for full chair movement:
73"L (185cm) x 46"W (117cm) x 65"H (165cm)

Spa requires 24" (61cm) of space between pedicure spa and wall
NOTE: Due to our policy of continuous improvements, all specifications are subject to change without notice.

